DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS D350-578 REV. H AND EARLIER AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D350-578 REV. 3 AND EARLIER

REF TCCA STC: SH93-4
REF FAA STC: SR00028NY / SR00029NY

REF EASA STC: 10016984

REF ARGENTINA STC: CTS-0508.13(A) REF RUSSIA STC: CT107-350

To ensure compatibility between the D350-578-011/-013/-015/-017/-021 Bearpaw Installation and existing Aerazur Float System, customers are encouraged to procure DSI 9506-011 Installation Mod Kit listed below and perform the following deviations on installation. Refer to Figure 1.

- 1. Move each D2432F/D2432-3/D2672F/D4297-1/-3 Bearpaw aft by 1.50" max;
- 2. Substitute aftmost D2438 or D4011-1 Clamp with two D3171-3 Angles trimmed to fit the Aerazur Float Clamps on each D2432F/D2432-3/D2672F/D4297-1/-3 Bearpaw;
- 3. Add extra holes/counterbores (Ø0.260" thru, cbore Ø0.930" x 0.300" deep from bottom) on each D2432F/D2432-3/ D2672F/D4297-1/-3 Bearpaw to mount center D2438 or D4011-1 Clamp to clear aft crosstube saddle.
- 4. If installing/re-installing D350-578-031 Wearplate Kit, replace center clamp hardware per Figure 1. Note: Hardware listed is customer supplied.

In all other aspects, install the D350-578-011/-013/-015/-017/-021 Bearpaw Installation per Installation Instructions D350-578 Rev. H or earlier.

PARTS LIST



| QTY -011 | PART NUMBER | DESCRIPTION | | | |
|-------------|--------------|----------------------|--|--|--|
| Х | DSI 9506-011 | INSTALLATION MOD KIT | | | |
| 4 | D2274 | RADIUS BLOCK | | | |
| 4 | D2529 | WASHER | | | |
| 4 | D3171-3 | ANGLE | | | |
| 4 | AN4-12A | BOLT | | | |
| 4 | AN960JD416 | WASHER | | | |
| 4 | MS21042L4 | NUT | | | |

| CANADA | | | | | |
|-------------------------|--|--|--|--|--|
| DEPARTMENT OF TRANSPORT | | | | | |
| AIRCRAFT CERTIFICATION | | | | | |
| BRANCH | | | | | |
| DAO # 01-O-01 | | | | | |
| APPROVED | | | | | |
| D. SHEPHERD (DE # 02) | | | | | |
| DATE:16.07.15 | | | | | |
| CERT. NO.: SH93-4 | | | | | |
| ISSUE NO.:10 | | | | | |
| | | | | | |

| В | GENERAL REVISION. REVISED APPLICABILITY AND D3171-3 WAS D3171-1. REASON: PAR14-380. | | | | | 16.07.15 |
|---------------|---|------|-----|--|-----|--------------|
| Α | NEW IS | SSUE | | | MB | 10.02.26 |
| REV. | , D | | | ESCRIPTION | BY | DATE |
| DESIGN | | -41 | | DART AEROSP | ACE | LTD |
| DRAWN | | 4 | | HAWKESBURY, ONTAR | | |
| CHECK | ΞD | 112 | Tee | DRAWING NO. | | REV. B |
| MFG. AF | PR. | N/A | \ | DSI 9506 | | SHEET 1 OF 2 |
| APPRO | √ED | 100 | 8 | TITLE | | SCALE |
| DE APP | R. | # | _ | INSTALL MODIFICATION | | NTS |
| DATE 16.07.15 | | | - | COPYRIGHT © 2010 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLED ON THE EXPRESS CONDITION THAT IT IS NOT TO SE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO MAY OTHER PERSON WITHOUT WITTEN PERSONSION FROM DAY LARDROPACE LTD. | | |




FIGURE 1: INSTALL MOD

(AERAZUR FLOAT AND HARDWARE NOT SHOWN FOR CLARITY)



| DESIGN A | | DART AEROSPACE LTD | | |
|------------|-------|--|--------------|--|
| DRAWN | 4 | HAWKESBURY, ONTARIO, CANADA | | |
| CHECKED | Mee | DRAWING NO. | REV. B | |
| MFG. APPR. | N/A | DSI 9506 | SHEET 2 OF 2 | |
| APPROVED | (Ph) | TITLE | SCALE | |
| DE APPR. | -# | INSTALL MODIFICATION | NTS | |
| DATE 16.0 | 07.15 | COPYRIGHT © 2010 BY DART AEROSPACE LTD THIS DOCUMENT IS PROVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE PROPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPYED OR COMMUNICATED TO JAIN OTHER PERSON WITHOUT WRITTEN PERSISSON FROM DAYLE ARROSPACE LTD. | | |